



**Singleton
Corporation**

3280 West 67th Place
Cleveland, OH 44102-5241
phone: 216.651.7800 fax: 216.651.4247

Water Immersion Test Tanks

- ½"-1" Thick Polypropylene Walls and Bottom
- Fuse-Fab™ Welded Construction for Long-Lasting Performance, Structural Integrity and Maximum Strength
- Encapsulated Steel-Core™ Reinforced Rim and Girth(s)
- Mild steel, painted stand
- Drain fitting with shut-off valve
- Manual Removable Flat Cover with Handles

OPTIONAL

- Air Spring Cover Lifter
- Digital Temperature Controllers
- Low Water Sensor System
- Timed Lift Device



125 gallon capacity on a stand



WITT 50 with Lift Device

WITT Tanks ¾ Immersion Test Tanks for Water Immersion, 5% Salt Solution Testing. The tanks meet ASTM D870 specifications as well as other similar testing requirements.

Capacity: 50, 75, 100, 125, 150 gallon or — *made to order*
Temperature range: Titanium electric immersion heater(s) up to 140°F
Test Material: Electrolyte salt solution
Agitation: Air agitation sparger with regulator (optional)
Designed for: ASTM D870
Optional: Specimen support racks, pneumatic cover opening, timer, lifting device, heater